


TECHNICAL INFORMATION

FOR PROFESSIONAL USE ONLY

<p>MEDIUM CUT POLISHING COMPOUND</p>	
<p>Art. No.</p>	
<p>16338 (1 kg) 16335 (250 g)</p>	
<p>COLOUR: grey</p>	
<p>DENSITY: 1,12 g/cm³</p>	

PRODUCT DESCRIPTION

Premium class polishing compound with medium cutting power. Designed to remove medium scratches and P2000 grit sanding marks. The unique formula based on the highest quality ingredients ensures effective removal of imperfections while giving the surface a high gloss finish. The product does not contain fillers, silicones or waxes.

- Removes P2000 grit sand traces.
- High performance.
- Easy to use.
- Applicable on both fresh and fully polymerized paints.

- Cut level: 6/10
- Gloss level: 8/10
- Processing: manual work, mechanical work (rotary, Dual Action)

RECOMMENDED APPLICATORS

- BRAYT POLISHING FOAM SOFT grey
- BRAYT LAMBSWOOL „D” yellow
- BRAYT LAMBSWOOL „MM” white
- BRAYT ORANGE PEEL REMOVAL PADS: „JEANS”, „CORDUROY”

USE

- On hard and scratch-resistant lacquers, use the compound with a lambswool or hard polishing foam.
- Apply small amount of polishing compound on the polishing pad or surface to be treated.
- When using a new polishing pad, it is recommended to apply the compound on the applicator and pre-polish the surface.
- Polish in a speed range of 1200 – 1600 RPM, applying light or medium pressure.
- Polish until all scratches have been removed.
- Remove all polishing compound residue using microfiber cloth.
- When polishing large surfaces, it is recommended to polish smaller sections at a time.

To obtain higher gloss use the polishing compound PERFECT FINISH in the second polishing step.

STORAGE

Store the product in tightly closed container at 0 - 45°C. Keep away from heat, fire and direct sunlight. Close the containers immediately after each use. Protect from frost. Keep away from children.

WARRANTY PERIOD

MEDIUM CUT

24 months from production date

LIMITATION OF LIABILITY

The information contained in this TDS sheet is up-to-date and correct on the day the information is released. Because TROTON cannot control or predict the conditions under which a product will be used, each user should review the information in the specific context of the intended usage. To the maximum extent permitted by applicable law, TROTON shall not be liable for damages of any kind arising from the use or reliance on information contained in this TDS.

Given the variety of factors that can affect the usage and application of the TROTON product, some of which are only within the user's knowledge and control range, it is essential that the user evaluate the TROTON product to determine if the product is fit for a particular purpose and whether the product is suitable for the user's usage.

Under no circumstances shall TROTON be liable to the user or any third party for any indirect, derivative, incidental, special or punitive damages, including loss of profits resulting from the use of products manufactured by TROTON and / or TROTON's services.

All information is based on meticulous laboratory tests and many years of experience. An established position on the market does not release us from continuous quality control of our products. However, we are not responsible for the final effects of improper storage or use of our products and for work that is not in line with good craftsmanship.

TROTON Sp. z o.o.
Ząbrowo, Poland.