

PUTTY FOR WOOD NATURAL

Printing: 28/05/2024 Date of compilation: 10/05/2024 Version: 1

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier:** PUTTY FOR WOOD NATURAL
Other means of identification:
UFI: 61VD-N1M3-R00K-FF2K
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**
Relevant uses: Car repair. For professional users/industrial user only.
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**
Troton Sp. z o.o.
Ząbrowo 14A
78-120 Gościno - Zachodniopomorskie - Polska
Phone: +48 94 35 123 94 - Fax: +48 94 35 126 22
troton@troton.com.pl
www.troton.pl / www.troton.eu
- 1.4 Emergency telephone number:** (8am-4pm)+48 094 35 123 94; 112

SECTION 2: HAZARDS IDENTIFICATION

- 2.1 Classification of the substance or mixture:**
CLP Regulation (EC) No 1272/2008:
Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.
Eye Irrit. 2: Eye irritation, Category 2, H319
Flam. Liq. 3: Flammable liquids, Category 3, H226
Repr. 2: Reproductive toxicity, Category 2, H361d
Skin Irrit. 2: Skin irritation, Category 2, H315
Skin Sens. 1A: Sensitisation, skin, Category 1A, H317
STOT RE 1: Specific target organ toxicity — Repeated exposure, Hazard Category 1 (Inhalation), H372

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:

Danger



Hazard statements:

Eye Irrit. 2: H319 - Causes serious eye irritation.
Flam. Liq. 3: H226 - Flammable liquid and vapour.
Repr. 2: H361d - Suspected of damaging the unborn child.
Skin Irrit. 2: H315 - Causes skin irritation.
Skin Sens. 1A: H317 - May cause an allergic skin reaction.
STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure (Inhalation).

Precautionary statements:

P201: Obtain special instructions before use.
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280: Wear protective gloves/protective clothing/respiratory protection/eye protection/protective footwear.
P302+P352: IF ON SKIN: Wash with plenty of water.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313: IF exposed or concerned: Get medical advice/attention.
P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively.

Supplementary information:

EUH211: Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Substances that contribute to the classification

styrene; maleic anhydride

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

PUTTY FOR WOOD NATURAL

Printing: 28/05/2024

Date of compilation: 10/05/2024

Version: 1

SECTION 2: HAZARDS IDENTIFICATION (continued)

2.3 Other hazards:

Product does not meet PBT/vPvB criteria
Endocrine-disrupting properties: The product does not meet the criteria.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Mixture composed of chemical products

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification	Concentration
CAS: 100-42-5 EC: 202-851-5 Index: 601-026-00-0 REACH: 01-2119457861-32-XXXX	styrene⁽¹⁾ Self-classified	10 - <25 %
	Regulation 1272/2008 Acute Tox. 4: H332; Aquatic Chronic 3: H412; Asp. Tox. 1: H304; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Repr. 2: H361d; Skin Irrit. 2: H315; STOT RE 1: H372; STOT SE 3: H335 - Danger	
CAS: 7727-43-7 EC: 231-784-4 Index: Non-applicable REACH: 01-2119491274-35-XXXX	Barium Sulfate⁽²⁾ Not classified	5 - <10 %
	Regulation 1272/2008	
CAS: 13463-67-7 EC: 236-675-5 Index: 022-006-00-2 REACH: 01-2119489379-17-XXXX	Titanium dioxide (aerodynamic diameter ≤ 10 µm)⁽¹⁾ ATP ATP14	1 - <2,5 %
	Regulation 1272/2008 Carc. 2: H351 - Warning	
CAS: 14808-60-7 EC: 238-878-4 Index: Non-applicable REACH: Non-applicable	Quartz (1 % < RCS < 10%)⁽²⁾ Self-classified	<1 %
	Regulation 1272/2008 STOT RE 2: H373 - Warning	
CAS: 108-31-6 EC: 203-571-6 Index: 607-096-00-9 REACH: 01-2119472428-31-XXXX	maleic anhydride⁽¹⁾ ATP ATP13	<1 %
	Regulation 1272/2008 Acute Tox. 4: H302; Eye Dam. 1: H318; Resp. Sens. 1: H334; Skin Corr. 1B: H314; Skin Sens. 1A: H317; STOT RE 1: H372; EUH071 - Danger	

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

⁽²⁾ Substance with a Union workplace exposure limit

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Other information:

Identification	Specific concentration limit
maleic anhydride CAS: 108-31-6 EC: 203-571-6	% (w/w) >=0,001: Skin Sens. 1A - H317

Acute toxicity estimate for the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or as determined in accordance with Annex I to that Regulation:

Identification	Acute toxicity	Genus
maleic anhydride CAS: 108-31-6 EC: 203-571-6	LD50 oral	1090 mg/kg
	LD50 dermal	Not relevant
	LC50 inhalation	Not relevant

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

PUTTY FOR WOOD NATURAL

Printing: 28/05/2024

Date of compilation: 10/05/2024

Version: 1

SECTION 4: FIRST AID MEASURES (continued)

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Not relevant

SECTION 5: FIREFIGHTING MEASURES**5.1 Extinguishing media:****Suitable extinguishing media:**

Foam extinguisher (AB), Dry Chemical Powder (ABC) Fire Extinguisher, Carbon dioxide extinguisher (BC)

Unsuitable extinguishing media:

Water jet

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES**6.1 Personal precautions, protective equipment and emergency procedures:****For non-emergency personnel:**

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

- CONTINUED ON NEXT PAGE -

PUTTY FOR WOOD NATURAL

Printing: 28/05/2024

Date of compilation: 10/05/2024

Version: 1

SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

It is recommended to avoid environmental spillage of both the product and its container.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE**7.1 Precautions for safe handling:****A.- General precautions for safe use**

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

PREGNANT WOMEN SHOULD NOT BE EXPOSED TO THIS PRODUCT. Transfer in designated areas that comply with the necessary safety conditions (emergency showers and eyewash stations in close proximity), using personal protection equipment, especially on the hands and face (See section 8). Limit manual transfers to small amounts only. Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:**A.- Specific storage requirements**

Minimum Temp.: 15 °C

Maximum Temp.: 25 °C

Maximum time: 12 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1 Control parameters:**

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

PUTTY FOR WOOD NATURAL

Printing: 28/05/2024

Date of compilation: 10/05/2024

Version: 1

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification	Occupational exposure limits		
Barium Sulfate CAS: 7727-43-7 EC: 231-784-4	IOELV (8h)		0,5 mg/m ³
	IOELV (STEL)		
Quartz (1 % < RCS < 10%) CAS: 14808-60-7 EC: 238-878-4	IOELV (8h)		0,1 mg/m ³
	IOELV (STEL)		

DNEL (Workers):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
styrene CAS: 100-42-5 EC: 202-851-5	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	406 mg/kg	Not relevant
	Inhalation	289 mg/m ³	306 mg/m ³	85 mg/m ³	Not relevant
Barium Sulfate CAS: 7727-43-7 EC: 231-784-4	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	Not relevant	Not relevant
	Inhalation	Not relevant	Not relevant	10 mg/m ³	10 mg/m ³
maleic anhydride CAS: 108-31-6 EC: 203-571-6	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	Not relevant	Not relevant
	Inhalation	0,2 mg/m ³	0,2 mg/m ³	0,081 mg/m ³	0,081 mg/m ³

DNEL (General population):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
styrene CAS: 100-42-5 EC: 202-851-5	Oral	Not relevant	Not relevant	2,1 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	343 mg/kg	Not relevant
	Inhalation	174,25 mg/m ³	182,75 mg/m ³	10,2 mg/m ³	Not relevant
Barium Sulfate CAS: 7727-43-7 EC: 231-784-4	Oral	Not relevant	Not relevant	13000 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	Not relevant	Not relevant
	Inhalation	Not relevant	Not relevant	10 mg/m ³	Not relevant

PNEC:

Identification				
styrene CAS: 100-42-5 EC: 202-851-5	STP	5 mg/L	Fresh water	0,028 mg/L
	Soil	0,2 mg/kg	Marine water	0,014 mg/L
	Intermittent	0,04 mg/L	Sediment (Fresh water)	0,614 mg/kg
	Oral	Not relevant	Sediment (Marine water)	0,307 mg/kg
Barium Sulfate CAS: 7727-43-7 EC: 231-784-4	STP	62,2 mg/L	Fresh water	0,115 mg/L
	Soil	207,7 mg/kg	Marine water	Not relevant
	Intermittent	Not relevant	Sediment (Fresh water)	600,4 mg/kg
	Oral	Not relevant	Sediment (Marine water)	Not relevant
maleic anhydride CAS: 108-31-6 EC: 203-571-6	STP	44,6 mg/L	Fresh water	0,038 mg/L
	Soil	0,037 mg/kg	Marine water	0,004 mg/L
	Intermittent	0,379 mg/L	Sediment (Fresh water)	0,296 mg/kg
	Oral	Not relevant	Sediment (Marine water)	0,03 mg/kg

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

In accordance with the order of importance to control professional exposure (Directive 98/24/EC) it is recommended to use localized extraction in the work area as a collective protection measure to avoid exceeding the occupational exposure limits. In case of using personal protective equipment it should have CE marking in accordance with Directive 2016/425/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For additional information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



PUTTY FOR WOOD NATURAL

Printing: 28/05/2024



Date of compilation: 10/05/2024

Version: 1

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)



Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory respiratory tract protection	Filter mask for gases and vapours		EN 405:2002+A1:2010	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands





Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory hand protection	NON-disposable chemical protective gloves (Material: Nitrile, Breakthrough time: > 480 min, Thickness: 0.4 mm)		EN ISO 374-1:2016+A1:2018 EN 16523-1:2015+A1:2018 EN ISO 21420:2020	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.



D.- Eye and face protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory face protection	Panoramic glasses against splash/projections.		EN 166:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties		EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982-1:2004/A1:2010 EN ISO 6529:2013 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1994	For professional use only. Clean periodically according to the manufacturer's instructions.
 Mandatory foot protection	Safety footwear for protection against chemical risk, with antistatic and heat resistant properties		EN ISO 13287:2020 EN ISO 20345:2011 EN 13832-1:2019	Replace boots at any sign of deterioration.

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):	14,04 % weight
V.O.C. density at 20 °C:	60 kg/m ³ (60 g/L)
Average carbon number:	7,98
Average molecular weight:	104,25 g/mol

PUTTY FOR WOOD NATURAL

Printing: 28/05/2024 Date of compilation: 10/05/2024 Version: 1

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C:	Liquid
Appearance:	Viscous
Colour:	 Brown
Odour:	Characteristic
Odour threshold:	Not relevant *

Volatility:

Boiling point at atmospheric pressure:	113 °C
Vapour pressure at 20 °C:	2200 Pa
Vapour pressure at 50 °C:	11589,73 Pa (11,59 kPa)
Evaporation rate at 20 °C:	Not relevant *

Product description:

Density at 20 °C:	1789,9 - 1790,1 kg/m ³
Relative density at 20 °C:	1,651
Dynamic viscosity at 20 °C:	84,56 cP
Kinematic viscosity at 20 °C:	51,23 mm ² /s
Kinematic viscosity at 40 °C:	>20,5 mm ² /s
Concentration:	Not relevant *
pH:	Not relevant *
Vapour density at 20 °C:	Not relevant *
Partition coefficient n-octanol/water 20 °C:	Not relevant *
Solubility in water at 20 °C:	Not relevant *
Solubility properties:	Not relevant *
Decomposition temperature:	Not relevant *
Melting point/freezing point:	Not relevant *

Flammability:

Flash Point:	39 °C
Flammability (solid, gas):	Not relevant *
Autoignition temperature:	345 °C
Lower flammability limit:	Not available
Upper flammability limit:	Not available

Particle characteristics:

Median equivalent diameter:	Non-applicable
-----------------------------	----------------

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties:	Not relevant *
Oxidising properties:	Not relevant *
Corrosive to metals:	Not relevant *
Heat of combustion:	Not relevant *
Aerosols-total percentage (by mass) of flammable components:	Not relevant *

Other safety characteristics:

*Not relevant due to the nature of the product, not providing information property of its hazards.

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

PUTTY FOR WOOD NATURAL

Printing: 28/05/2024 Date of compilation: 10/05/2024 Version: 1

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)	
Surface tension at 20 °C:	Not relevant *
Refraction index:	Not relevant *
*Not relevant due to the nature of the product, not providing information property of its hazards.	

SECTION 10: STABILITY AND REACTIVITY											
10.1 Reactivity:	No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.										
10.2 Chemical stability:	Chemically stable under the indicated conditions of storage, handling and use.										
10.3 Possibility of hazardous reactions:	Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.										
10.4 Conditions to avoid:	Applicable for handling and storage at room temperature:										
	<table border="1"> <thead> <tr> <th>Shock and friction</th> <th>Contact with air</th> <th>Increase in temperature</th> <th>Sunlight</th> <th>Humidity</th> </tr> </thead> <tbody> <tr> <td>Not applicable</td> <td>Not applicable</td> <td>Risk of combustion</td> <td>Avoid direct impact</td> <td>Not applicable</td> </tr> </tbody> </table>	Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity	Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable
Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity							
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable							
10.5 Incompatible materials:	<table border="1"> <thead> <tr> <th>Acids</th> <th>Water</th> <th>Oxidising materials</th> <th>Combustible materials</th> <th>Others</th> </tr> </thead> <tbody> <tr> <td>Avoid strong acids</td> <td>Not applicable</td> <td>Avoid direct impact</td> <td>Not applicable</td> <td>Avoid alkalis or strong bases</td> </tr> </tbody> </table>	Acids	Water	Oxidising materials	Combustible materials	Others	Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases
Acids	Water	Oxidising materials	Combustible materials	Others							
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases							
10.6 Hazardous decomposition products:	Contains substances highly reactive and can auto-polymerize as a result of internal peroxide accumulation. The peroxides formed in these reactions are extremely shock- and heat-sensitive.										

SECTION 11: TOXICOLOGICAL INFORMATION	
11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:	The experimental information related to the toxicological properties of the product itself is not available
Dangerous health implications:	In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:
A- Ingestion (acute effect):	<ul style="list-style-type: none"> - Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3. - Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.
B- Inhalation (acute effect):	<ul style="list-style-type: none"> - Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3. - Corrosivity/Irritability: Prolonged inhalation of the product is corrosive to mucous membranes and the upper respiratory tract
C- Contact with the skin and the eyes (acute effect):	<ul style="list-style-type: none"> - Contact with the skin: Produces skin inflammation. - Contact with the eyes: Produces eye damage after contact.
D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):	<ul style="list-style-type: none"> - Carcinogenicity: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with carcinogenic effects. For more information see section 3. - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3. - Reproductive toxicity: Suspected of damaging the unborn child.

- CONTINUED ON NEXT PAGE -

PUTTY FOR WOOD NATURAL

Printing: 28/05/2024

Date of compilation: 10/05/2024

Version: 1

SECTION 11: TOXICOLOGICAL INFORMATION (continued)**E- Sensitizing effects:**

- Respiratory: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with sensitising effects. For more information see section 3.
- Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.

F- Specific target organ toxicity (STOT) - single exposure:

Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Serious health effects in the case of prolonged inhalation, including death, serious functional disorders or morphological changes of toxicological importance.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

CAS 13463-67-7 Titanium dioxide (aerodynamic diameter $\leq 10 \mu\text{m}$): The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter $\leq 10 \mu\text{m}$

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
	LD50 oral	LD50 dermal / LC50 inhalation	
styrene CAS: 100-42-5 EC: 202-851-5	LD50 oral	>2000 mg/kg	
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation	11,8 mg/L (4 h)	Rat
Titanium dioxide (aerodynamic diameter $\leq 10 \mu\text{m}$) CAS: 13463-67-7 EC: 236-675-5	LD50 oral	10000 mg/kg	Rat
	LD50 dermal	10000 mg/kg	Rabbit
	LC50 inhalation	>5 mg/L	
Barium Sulfate CAS: 7727-43-7 EC: 231-784-4	LD50 oral	>5000 mg/kg	Rat
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation	>5 mg/L	
Quartz (1 % < RCS < 10%) CAS: 14808-60-7 EC: 238-878-4	LD50 oral	>2000 mg/kg	
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation	>5 mg/L	
maleic anhydride CAS: 108-31-6 EC: 203-571-6	LD50 oral	1090 mg/kg	Rat
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation	>5 mg/L	

Acute Toxicity Estimate (ATE mix):

ATE mix		Ingredient(s) of unknown toxicity
Oral	>2000 mg/kg (Calculation method)	Non-applicable
Dermal	>2000 mg/kg (Calculation method)	Non-applicable
Inhalation	87,16 mg/L (4 h) (Calculation method)	0 %

11.2 Information on other hazards:**Endocrine disrupting properties**

Endocrine-disrupting properties: The product does not meet the criteria.

Other information

Not relevant

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

PUTTY FOR WOOD NATURAL

Printing: 28/05/2024

Date of compilation: 10/05/2024

Version: 1

SECTION 12: ECOLOGICAL INFORMATION (continued)

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

12.1 Toxicity:

Acute toxicity:

Identification	Concentration		Species	Genus
styrene CAS: 100-42-5 EC: 202-851-5	LC50	64,7 mg/L (96 h)	Carassius auratus	Fish
	EC50	4,7 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	67 mg/L (192 h)	Microcystis aeruginosa	Algae
Barium Sulfate CAS: 7727-43-7 EC: 231-784-4	LC50	76000 mg/L (96 h)	Salmo gairdneri	Fish
	EC50	Not relevant		
	EC50	Not relevant		

Chronic toxicity:

Identification	Concentration		Species	Genus
styrene CAS: 100-42-5 EC: 202-851-5	NOEC	Not relevant		
	NOEC	1,01 mg/L	Daphnia magna	Crustacean
Barium Sulfate CAS: 7727-43-7 EC: 231-784-4	NOEC	100 mg/L	Danio rerio	Fish
	NOEC	Not relevant		

12.2 Persistence and degradability:

Substance-specific information:

Identification	Degradability		Biodegradability	
styrene CAS: 100-42-5 EC: 202-851-5	BOD5	1,96 g O2/g	Concentration	100 mg/L
	COD	2,8 g O2/g	Period	14 days
	BOD5/COD	0,7	% Biodegradable	100 %
maleic anhydride CAS: 108-31-6 EC: 203-571-6	BOD5	Not relevant	Concentration	33,33 mg/L
	COD	Not relevant	Period	29 days
	BOD5/COD	Not relevant	% Biodegradable	98,19 %

12.3 Bioaccumulative potential:

Substance-specific information:

Identification	Bioaccumulation potential	
styrene CAS: 100-42-5 EC: 202-851-5	BCF	14
	Pow Log	2.95
	Potential	Low
maleic anhydride CAS: 108-31-6 EC: 203-571-6	BCF	
	Pow Log	-2.61
	Potential	

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
styrene CAS: 100-42-5 EC: 202-851-5	Koc	Not relevant	Henry	Not relevant
	Conclusion	Not relevant	Dry soil	Not relevant
	Surface tension	3,21E-2 N/m (25 °C)	Moist soil	Not relevant
maleic anhydride CAS: 108-31-6 EC: 203-571-6	Koc	42	Henry	OE+0 Pa·m ³ /mol
	Conclusion	Very High	Dry soil	Not relevant
	Surface tension	1,673E-2 N/m (250,21 °C)	Moist soil	Not relevant

12.5 Results of PBT and vPvB assessment:

Product does not meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product does not meet the criteria.

12.7 Other adverse effects:

Not described

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

PUTTY FOR WOOD NATURAL

Printing: 28/05/2024

Date of compilation: 10/05/2024

Version: 1

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 01 11* 15 01 10*	waste paint and varnish containing organic solvents or other hazardous substances packaging containing residues of or contaminated by hazardous substances	Hazardous

Type of waste (Regulation (EU) No 1357/2014):

HP3 Flammable, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP10 Toxic for reproduction, HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-hazardous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2023 and RID 2023:



- 14.1 UN number or ID number:** UN1866
- 14.2 UN proper shipping name:** RESIN SOLUTION
- 14.3 Transport hazard class(es):** 3
Labels: 3
- 14.4 Packing group:** III
- 14.5 Environmental hazards:** No
- 14.6 Special precautions for user**
Special regulations: Not relevant
Tunnel restriction code: D/E
Physico-Chemical properties: see section 9
Limited quantities: 5 L
- 14.7 Maritime transport in bulk according to IMO instruments:** Not relevant

Transport of dangerous goods by sea:

With regard to IMDG 41-22:



- 14.1 UN number or ID number:** UN1866
- 14.2 UN proper shipping name:** RESIN SOLUTION
- 14.3 Transport hazard class(es):** 3
Labels: 3
- 14.4 Packing group:** III
- 14.5 Marine pollutant:** No
- 14.6 Special precautions for user**
Special regulations: 955, 223
EmS Codes: F-E, S-E
Physico-Chemical properties: see section 9
Limited quantities: 5 L
Segregation group: Not relevant
- 14.7 Maritime transport in bulk according to IMO instruments:** Not relevant

Transport of dangerous goods by air:

- CONTINUED ON NEXT PAGE -

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

PUTTY FOR WOOD NATURAL

Printing: 28/05/2024

Date of compilation: 10/05/2024

Version: 1

SECTION 14: TRANSPORT INFORMATION (continued)

With regard to IATA/ICAO 2024:



- 14.1 UN number or ID number:** UN1866
14.2 UN proper shipping name: RESIN SOLUTION
14.3 Transport hazard class(es): 3
 Labels: 3
14.4 Packing group: III
14.5 Environmental hazards: No
14.6 Special precautions for user
 Physico-Chemical properties: see section 9
14.7 Maritime transport in bulk according to IMO instruments: Not relevant

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

- Article 95, REGULATION (EU) No 528/2012: *ethanol (64-17-5) - PT: (1,2,4,6); propan-2-ol (67-63-0) - PT: (1,2,4)*
- Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Not relevant
- Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Not relevant
- REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Not relevant
- Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Not relevant

Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements
P5c	FLAMMABLE LIQUIDS	5000	50000

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Laboral exposure to respirable crystalline silica must be controlled in accordance with Directive (EU) 2022/431, of the European Parliament and of the Council, of March 9, 2022, amending Directive 2004/37/EC, relating to the protection of workers against risks related to exposure to carcinogens or mutagens during work.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

Not relevant

Texts of the legislative phrases mentioned in section 2:

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

PUTTY FOR WOOD NATURAL

Printing: 28/05/2024

Date of compilation: 10/05/2024

Version: 1

SECTION 16: OTHER INFORMATION (continued)

H315: Causes skin irritation.
H361d: Suspected of damaging the unborn child.
H372: Causes damage to organs through prolonged or repeated exposure (Inhalation).
H317: May cause an allergic skin reaction.
H226: Flammable liquid and vapour.
H319: Causes serious eye irritation.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Acute Tox. 4: H302 - Harmful if swallowed.
Acute Tox. 4: H332 - Harmful if inhaled.
Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.
Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.
Carc. 2: H351 - Suspected of causing cancer (Inhalation).
Eye Dam. 1: H318 - Causes serious eye damage.
Eye Irrit. 2: H319 - Causes serious eye irritation.
Flam. Liq. 3: H226 - Flammable liquid and vapour.
Repr. 2: H361d - Suspected of damaging the unborn child.
Resp. Sens. 1: H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin Corr. 1B: H314 - Causes severe skin burns and eye damage.
Skin Irrit. 2: H315 - Causes skin irritation.
Skin Sens. 1A: H317 - May cause an allergic skin reaction.
STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure (Inhalation).
STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Inhalation).
STOT SE 3: H335 - May cause respiratory irritation.

Classification procedure:

Skin Irrit. 2: Calculation method
Repr. 2: Calculation method
STOT RE 1: Calculation method
Skin Sens. 1A: Calculation method
Flam. Liq. 3: Calculation method (2.6.4.3)
Eye Irrit. 2: Calculation method

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

<http://echa.europa.eu>
<http://eur-lex.europa.eu>

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road
IMDG: International maritime dangerous goods code
IATA: International Air Transport Association
ICAO: International Civil Aviation Organisation
COD: Chemical Oxygen Demand
BOD5: 5day biochemical oxygen demand
BCF: Bioconcentration factor
LD50: Lethal Dose 50
LC50: Lethal Concentration 50
EC50: Effective concentration 50
LogPOW: Octanolwater partition coefficient
Koc: Partition coefficient of organic carbon
UFI: unique formula identifier
IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -