


TECHNICAL INFORMATION

FOR PROFESSIONAL USE ONLY

<p>i11 POLISHING COMPOUND</p>	
<p>Art. No.</p>	
<p>11753 (1kg) 11541 (4,5kg)</p>	
<p>COLOUR: white</p>	
<p>DENSITY: about 1,22 g/cm³</p>	

PRODUCT DESCRIPTION

i11 is a polishing compound designed for polyester (PE), polyurethane (PU), acrylic, and water-based paints. Simple and easy to use. It ensures an ideal Surface without hidden defects and artificial glossing. It allows for the quick removal of sanding marks. Thanks to high-quality polishing minerals, it enables a good gloss in a short time without excessive heating of the surface. It does not contain wax fillers or silicones.

- Cut Level: 7/10
- Gloss level: 7/10
- Processing: manual work, rotary machine

USE

- Remove surface defects with P800 to P1000 sanding paper (depending on the surface hardness). For hard gelcoats and dark colors it's recommended to use P1200 to P2000 grit sanding paper. The basic rule is to make the finishing with the highest grit of sanding paper, so the polishing process will be shortened to maximum with very good quality of surface.
- Wash the surface to be treated.
- Polish using rotary polishing machine with adjustable speed.
- Apply polishing compound on the surface or polishing pad (polishing wool or hard polishing foam).
- Spread compound on the surface with min. RPM (800 – 1000 RPM).
- Polish until colour and consistency of compound will be changed.
- Slowly increase the speed to max. 1600 RPM and polish the surface with light pressure.
- Polish until remove the scratches and getting perfect shine.
- Remove the compound residue with clean microfiber cloth.

APPLICATORS

Polishing compound i11 is recommended for use with Troton polishing foam or wool.

STORAGE

Store the product in tightly closed container at 0 - 45°C. Keep away from heat, fire and direct sunlight. Close the containers immediately after each use. Protect from frost. Keep away from children.

EXPIRY DATE

i11 Polishing compound	24 months from production date
------------------------	--------------------------------

LIMITATION OF LIABILITY

The information contained in this TDS sheet is up-to-date and correct on the day the information is released. Because TROTON cannot control or predict the conditions under which a product will be used, each user should review the information in the specific context of the intended usage. To the maximum extent permitted by applicable law, TROTON shall not be liable for damages of any kind arising from the use or reliance on information contained in this TDS.

Given the variety of factors that can affect the usage and application of the TROTON product, some of which are only within the user's knowledge and control range, it is essential that the user evaluate the TROTON product to determine if the product is fit for a particular purpose and whether the product is suitable for the user's usage.

Under no circumstances shall TROTON be liable to the user or any third party for any indirect, derivative, incidental, special or punitive damages, including loss of profits resulting from the use of products manufactured by TROTON and / or TROTON's services

TROTON Sp. z o.o.
Ząbrowo, Poland.